

What is claimed is:

1. A piezoelectric actuator comprising piezoelectric elements having different thicknesses stacked on one another.
2. A piezoelectric actuator according to Claim 1 which is distorted when a driving signal is input to generate a driving force and in which a piezoelectric element located at a side of the piezoelectric actuator with greater distortion has a thickness smaller than that of a piezoelectric element located at a side of the piezoelectric actuator with smaller distortion.
3. A piezoelectric actuator according to Claim 1, wherein at least two of the piezoelectric elements generate vibrations in the same direction.
4. A piezoelectric actuator according to Claim 1, wherein the piezoelectric elements are stacked in a direction in parallel with an output portion of the piezoelectric actuator.
5. A piezoelectric actuator according to Claim 1, wherein the piezoelectric elements are stacked in a direction perpendicular to the output portion of the piezoelectric actuator.
6. A piezoelectric actuator according to Claim 1, wherein the piezoelectric elements are piezoelectric elements for generating a plurality of different vibrations which are synthesized to be used as a driving force.
7. A piezoelectric actuator according to Claim 6, wherein the plurality of different vibrations of the piezoelectric

Q1
Cont.

elements are generated by respective separate piezoelectric elements.

8. A piezoelectric actuator according to Claim 1, wherein the piezoelectric elements include a piezoelectric element for detecting a vibration and wherein the piezoelectric element for detecting a vibration has a thickness different from those of the other piezoelectric elements.

9. An ultrasonic motor comprising:

a piezoelectric actuator formed by stacking piezoelectric elements having different thicknesses; and

a vibrator having the same thickness as that of the piezoelectric actuator vibrated by a vibration of the piezoelectric actuator.

10. A piezoelectric sensor comprising a piezoelectric actuator formed by stacking piezoelectric elements having different thicknesses.

11. A piezoelectric sensor according to Claim 10 wherein the piezoelectric actuator is distorted when a driving signal is input to generate a driving force and wherein a piezoelectric element located at a side of the piezoelectric actuator with greater distortion has a thickness smaller than that of a piezoelectric element located at a side of the piezoelectric actuator with smaller distortion.

12. An electronic apparatus with a piezoelectric actuator, comprising a piezoelectric actuator according to Claim 1.

Q1
Q2
Q3
Q4
Q5
Q6
Q7
Q8
Q9
Q10
Q11
Q12
Q13
Q14
Q15
Q16
Q17
Q18
Q19
Q20
Q21
Q22
Q23
Q24
Q25
Q26
Q27
Q28
Q29
Q30
Q31
Q32
Q33
Q34
Q35
Q36
Q37
Q38
Q39
Q40
Q41
Q42
Q43
Q44
Q45
Q46
Q47
Q48
Q49
Q50
Q51
Q52
Q53
Q54
Q55
Q56
Q57
Q58
Q59
Q60
Q61
Q62
Q63
Q64
Q65
Q66
Q67
Q68
Q69
Q70
Q71
Q72
Q73
Q74
Q75
Q76
Q77
Q78
Q79
Q80
Q81
Q82
Q83
Q84
Q85
Q86
Q87
Q88
Q89
Q90
Q91
Q92
Q93
Q94
Q95
Q96
Q97
Q98
Q99
Q100

SUB
Q2

A2
Cont.

13. An electronic apparatus with a piezoelectric sensor,
comprising a piezoelectric sensor according to Claim 10.

add
a3

add
B5

add
C3

add
D5